



AG1861500WTU

18oz Tan Uncoated Fiberglass Fabric
with Tucked Edges

Features

- High-temperature resistant tan uncoated fiberglass fabric.
- Chemical, oil, and corrosion resistant.
- Suitable for multiple welding, brazing, and soldering applications.
- May protect equipment from damage caused by sparks, heat, spatter, and more.
- Medium-high abrasion resistance.
- Temperature rating up to 1000°F
- Packaged individually, 2 rolls per pallet.

Technical Specifications

- **Weave:** PLAIN
- **Yarn:** WARP: ET9 430 tex; WEFT: ET9 430 tex
- **Length:** 500 yds
- **Width:** 61"
- **Weight as per ASTM-D3776-2009:** 580 g / m²
- **Ounces per Square Yard:** 18
- **Thickness as per ASTM-D1777-1996:** 0.75 mm
- **Thread count per cm as per ASTM-D3775-2008:** WARP: 8; WEFT: 5.7
- **Coating:** Uncoated, Tan
- **Total Weight as per ASTM-D3776-2009:** 580 g / m²
- **Total Thickness as per ASTM-D1777-1996:** 0.75 mm
- **Tensile Strength as per ASTM-D5034-2001:** WARP: 1200 N/2.5 cm; WEFT: 800 N/2.5 cm
- **Service Temperature:** 550 °C
- **Certifications:** Europe BSEN 476 part 7, European Union CE