



## AG246050WWU

24oz White Uncoated Fiberglass  
Fabric

### Features

- 24oz Heat Cleaned fiberglass fabric
- High-temperature resistant tan uncoated fiberglass fabric
- Chemical, oil, and corrosion resistant
- Suitable for multiple welding, brazing, and soldering applications
- Can be made to aluminum, neoprene, dyeing coating; welding blankets
- May protect equipment from damage caused by sparks, heat, spatter, and more
- Low bulk density, insulation, medium-high abrasion & oxidation resistance
- 100% not including asbestos elements
- Temperature rating up to 1000°F
- Packaged individually, 12 rolls per pallet

### Technical Specifications

- **Weave:** Plain
- **Thickness:** .05 in
- **Yarn:** **WARP:** ETG 5.81 tex; **WEFT:** ETG 5.81 tex
- **Tensile Strength:** **WARP:** 333 lb./in; **WEFT:** 222 lb./in
- **Thread Count:** **WARP:** 15 /in; **WEFT:** 8.5 /in
- **Length:** 50 yds (45.72 m)
- **Width:** 60" (1.524 m)
- **Weight:** 24 oz/yd<sup>2</sup>
- **Coating:** Uncoated, White
- **Service Temperature:** 550 °C (1022 °F)
- **Certifications:** Europe BSEN 476 part 7, European Union CE, America FM/ANSI 4950