SPECIFICATION SHEET

TECHNIWELD



AG326050WRS

32oz Red Silicone Coated Fiberglass Fabric

Features

- High-temperature resistant red silicone coated fiberglass fabric.
- Chemical, oil, and corrosion resistant.
- Suitable for multiple welding, brazing, and soldering applications.
- May protect equipment from damage caused by sparks, heat, spatter, and more.
- Medium-high abrasion resistance. •
- Temperature rating up to 1000°F
- Packaged individually, 12 rolls per pallet.

Technical Specifications

- Weave: 8 HS SATIN •
- Yarn: WARP: ET9 68 2x2 tex; WEFT: ET9 68 2x2 tex
- Length: 50 yds (45.72 m) •
- Width: 60" (1.524 m)
- Weight: 32 oz/yd² •
- Coating: Silicone Coated, Red •
- Coating Weight: 200 g / m^2 (5.90 oz/yd²) •
- Service Temperature: 550 °C (1022 °F)
- Certifications: Europe BSEN 476 part 7, European Union CE, America FM/ANSI 4950

TECHNIWELDUSA / www.techniweldusa.com

6205 Boat Rock Blvd. SW, Atlanta, Georgia 30336-2727 | Toll Free: (800) 445-2152 sales@techniweldusa.com Fax: (404) 699-7800