



AGWB356X6WU

35oz Uncoated White Fiberglass Welding Blanket

Features

- High-temperature resistant uncoated white fiberglass fabric.
- Chemical, oil, and corrosion resistant.
- Suitable for multiple welding, brazing, and soldering applications.
- May protect equipment from damage caused by sparks, heat, spatter, and more.
- Medium-high abrasion resistance.
- Temperature rating up to 1000°F

Technical Specifications

- **Weave:** PLAIN
- **Yarn:** WARP: ET9 860 tex; WEFT: ET9 860 tex
- **Length:** 6'
- **Width:** 6'
- **Weight as per ASTM-D3776-2009:** 1190 g / m²
- **Ounces per Square Yard:** 35
- **Thickness as per ASTM-D1777-1996:** 2 mm
- **Thread count per cm as per ASTM-D3775-2008:** WARP: 6; WEFT: 3.8
- **Coating:** Uncoated, White
- **Total Weight as per ASTM-D3776-2009:** 1190 g / m²
- **Total Thickness as per ASTM-D1777-1996:** 2 mm
- **Tensile Strength as per ASTM-D5034-2001:** WARP: 1200 N/2.5 cm; WEFT: 800 N/2.5 cm
- **Service Temperature:** 550 °C
- **Certifications:** Europe BSEN 476 part 7, European Union CE, America FM/ANSI 4950