



CSMGALV

Zinc Galvanized Spray-Matte Finish

Features

- Rustproofs metals exposed to corrosion or rust
- Electro-Chemically bonds with metals, stops rust creepage
- 95% pure-zinc
- Sprays on cold, protects surface from rust
- Self-healing
- Alternative to hot dip galvanize
- Meets specs: MIL-P-26915A, MILT26433, MIL-P-21035, MIL-P-46105, ASTM-A780

Technical Specifications

- **Material:** Zinc
- **Weight:** 14 oz
- **Packaging:** 12/box
- **Country of origin:** United States

Applications

- Welding
- Pipelines
- Power Plants
- Radiators
- Transformer Tanks
- Refineries

Usage Instructions

- Hold spray can upright about a foot away, and apply thin, even coats to the surface.
- Allow approximately 15 minutes to dry between coats, and 6 hours to dry completely before adding a top coat.

Warnings

CAUTION! Contains 2-Propanone (CAS#67-64-1), Propane/Isobutane/N-butane (CAS#68476-86-8), Zinc Rich Primer (mixture), Zinc powder (CAS#7440-66-6), Dimethylbenzene (CAS#1330-20-7), Ethylbenzene (CAS#100-41-4), Aluminum flake (CAS#7429-90-5), Stoddard solvent (CAS#8052-41-3), Aromatic hydrocarbon (CAS#64742-95-6), Toluene (CAS#108-88-3).

CONTENTS UNDER PRESSURE. Do not incinerate, puncture, store in direct sunlight or in temperatures above 120°F. Avoid prolonged breathing of fumes or mist. Use in well ventilated area. Do not spray on an open flame or other ignition source.

Extremely Flammable.

Harmful or fatal if swallowed, do not induce vomiting. Call physician immediately!

If accidentally sprayed in eyes, wash and flush with water for fifteen minutes.

KEEP OUT OF REACH OF CHILDREN.

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects (or other reproductive harm).

California Health & Safety Code §25249.5 et seq.

For Additional Product Health and Safety Information See Material Safety Data Sheet.