



HSI14XRLG

1/4" X 800' Single Line Green Hose Reel

Features

- Premium Flexible Gas Hose
- Premium Burst Resistant Fibered composition
- American Quality Control
- Ozone Resistant
- Aging Resistant
- Limited Oil Resistance (Acetylene Only)

Technical Specifications

- Tube Material: EPDM Compound
- Cover Material: EPDM Compound
- Cover: Corrugated
- Reinforced: Spiral Polyester Yarns
- Working Pressure: 200 PSI
- Burst Pressure: 800 PSI
- Inner Diameter: 1/4" ± 1/50" (6.3 mm ± 0.5 mm)
- Outer Diameter: 17/32" ± 1/50" (13 mm ± 0.5 mm)
- Length: 800'
- Inner and Outer Diameter Tolerance: 0.5 mm
- Temperature Range: -13° F (-25° C) 176° F (80° C)
- Color: Green
- For Use With: Oxygen
- Compliance: EN ISO3821

Applications

- Manufacturing Architectural and Structural Metals, Mining, Agricultural, Motor Vehicles, Aerospace, Shipbuilding
- Construction Residential, Commercial, Bridges, Dams, Utilities
- Or any other industry where welders may work

Usage Instructions

- Connect the hose to the regulator and torch body.
- Tighten all connection nuts firmly with a wrench making sure the system is leak-tight.

